

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number
WO 03/106103 A1(51) International Patent Classification:
B25C 11/00, B25D 1/04, F16B 15/00

B23P 19/04,

(74) Agent: ELLIS Terry J.; Ellis Enz Splits "LLC", 1480
Riverview Drive, Lima, Oh 45805 (US).

(21) International Application Number: PCT/US03/18806

(22) International Filing Date: 16 June 2003 (16.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/388,778 14 June 2002 (14.06.2002) US(71) Applicant (for all designated States except US): ELLIS
ENZ SPLITS, LLC. [US/US]; 1480 Riverview Drive,
Lima, OH 45805 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): PARENT, Stephen,
E. [US/US]; 10208 Springhurst Garden Circle, Louisville,
KY 40241 (US). DAY, Daniel, L. [US/US]; 10420 Glen-
mary Farm Drive, Louisville, KY 40291 (US).(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: SPIKED PLATE AND HAND TOOL FOR REMOVAL



(57) Abstract: A plate (10) with spikes (11) projecting therefrom to impale a log on respective opposite sides of a crack (20) in the end of the log and wherein the plate has pull tabs (18, 19) integral therewith and grippingly engageable by a tool (30) used to remove the plate from the end of the log. A tool for inserting and removing the plate from the log includes means (37) for driving and means (33) for removing the plate from the log including a slot (35) adjacent the impact end of the tool and into which the pull tab on the plate is inserted.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.